

Tesla : Model 3 : Dual Motor All Wheel Drive : Coil Suspension : 2017-19

Front : Left

Actual	Before	Specified Range
-0.4°	-0.4°	-1.0° -0.1°
5.5°	5.5°	4.7° 6.7°
-0.06°	-0.12°	-0.20° 0.10°
8.3°	8.3°	
7.9°	7.9°	

Front : Right

Actual	Before	Specified Range
-0.8°	-0.8°	-1.0° -0.1°
5.8°	5.8°	4.7° 6.7°
-0.05°	-0.12°	-0.20° 0.10°
8.7°	8.7°	
7.9°	7.9°	

Camber  
Caster  
Toe  
SAI  
Included Angle  
Turning Angle Diff.

Front

	Actual	Before	Specified Range
Cross Camber	0.4°	0.5°	-0.6° 0.6°
Cross Caster	-0.3°	-0.3°	-1.0° 1.0°
Cross SAI	-0.3°	-0.4°	
Total Toe	-0.11°	-0.24°	-0.40° 0.20°
Cross Turn Diff.			

Rear : Left

Actual	Before	Specified Range
-0.4°	-0.5°	-2.0° 0.0°
0.21°	-0.12°*	0.05° 0.35°

Rear : Right

Actual	Before	Specified Range
-1.0°	-1.0°	-2.0° 0.0°
0.20°	0.34°	0.05° 0.35°

Camber  
Toe

Rear

	Actual	Before	Specified Range
Cross Camber	0.6°	0.5°	-0.8° 0.8°
Total Toe	0.41°	0.22°	0.10° 0.70°
Thrust Angle	0.00°	-0.23°	-0.25° 0.25°
Axle Offset	0.0in	0.0in	

\* This value is not within specification. Tire wear, handling and safety problems may result.